

Meet the modular switchboard of the future

FlexSeT

Part of the Set Series



Stay one step ahead

Introducing FlexSeT™ – the low voltage switchboard of the future. FlexSeT's revolutionary design provides unparalleled flexibility to adapt to your customers' needs and build to project requirements even on-site. Featuring the exclusive I-Line stack for quick and familiar assembly, installation, and maintenance to better serve your customers. Available up to 2000A group mounted or 2500A fixed main breaker.

Unique features

- Flexible design and simplified ordering to better serve your specific project needs.
- Custom configuration via digital layout tools.
- Updated design features that simplify installation and maintenance.
- Digital assembly tools for authorized assemblers deliver UL quality confidence and unrivaled traceability.

The Square D FlexSeT low-voltage switchboard

Designed with the flexibility to help you confidently serve your customer's needs:



- FlexSeT reduces lead time with quick quote-to-order conversion. Be the partner your customers turn to for easily accessible solutions and delivery.
 - FlexSeT has your bases covered with design based on customer input and value.
 - I-Line based design delivers the enhanced quality, safety, and reliability you expect from Schneider Electric.
- UL/cUL approved, with first in the industry UL digital mark, provides you with peace of mind and confidence.
 - Flexible, modular design to easily accept connected offers and digitization capabilities means you can offer your customers the capability to grow with today's evolving market, as well as make change orders easy without impacting project schedules.
 - Distributed neutral simplifies wiring of neutral load connections by providing neutral access closer to the load the needs it.

Technical specifications

- Fixed Main breaker up to 2500A @ 80% rated
- Group mounted main breaker up to 2000A @ 80% rated
- Silver plated copper busbar material on all phases and ground
- System voltage up to:
 - * 600Y/347V 3Ph 4W 60 Hz
 - * 480Y/277 3Ph 4W 60 Hz
 - * 208Y/120V 3Ph 4W 60 Hz
- Maximum fault current rating 65kAIC
- Instrument compartment mounted devices (up to 480V):
 - * Maintenance Mode Switch
 - * 240kA Surge Protection
 - * PM5563 Meter
- I-Line with Plug-on Neutral
- 100% Rated Neutral throughout switchboard
- Left incoming only.
- NEMA-1 and NEMA-2 Enclosures
- Seismic Qualification- IBC 2012-2015 (ACE 7-10), NBCC 2015
- eCertifications: UL, CSA, NOM, IEC, CCC, and CE marked for global acceptance

se.com/us/flexset

Life Is On

Schneider
Electric

Schneider Electric
6700 Tower Cir #700,
Franklin, TN 37067